










Standard	Capacity	Internal dimensions	Door opening	Max. payload Tara weight	Max. EUR pallets
20' Dry Cargo (DC) 	33 cbm	Lenght 5.898 mm Width 2.352 mm Height 2.393 mm	Width 2.340 mm Height 2.280 mm	28.160 kgs 2.230 kgs	11
40' Dry Cargo (DC) 	67 cbm	Lenght 12.035 mm Width 2.352 mm Height 2.393 mm	Width 2.340 mm Height 2.280 mm	26.760 kgs 3.700 kgs	25
40' High Cube Dry Cargo (HC DC) 	76 cbm	Lenght 12.035 mm Width 2.352 mm Height 2.695 mm	Width 2.340 mm Height 2.577 mm	26.750 kgs 3.800 kgs	25
45' High Cube Dry Cargo (HC DC) 	85 cbm	Lenght 13.556 mm Width 2.352 mm Height 2.695 mm	Width 2.340 mm Height 2.577 mm	28.280 kgs 4.800 kgs	27
Reefer	Capacity	Internal dimensions	Door opening	Max. payload Tara weight	Max. EUR pallets
20' Reefer (RF) 	28 cbm	Lenght 5.451 mm Width 2.290 mm Height 2.157 mm	Width 2.286 mm Height 2.238 mm	27.490 kgs 2.990 kgs	10
40' High Cube Reefer (HC RF) 	67 cbm	Lenght 11.577 mm Width 2.290 mm Height 2.378 mm	Width 2.286 mm Height 2.535 mm	28.350 kgs 4.150 kgs	23
Open Top	Capacity	Internal dimensions	Top opening	Max. payload Tara weight	-
20' Open Top (OT) 	32 cbm	Lenght 5.919 mm Width 2.340 mm Height 2.286 mm	Lenght 5.425 mm Width 2.223 mm	28.230 kgs 2.177 kgs	-
40' Open Top (OT) 	64 cbm	Lenght 12.029 mm Width 2.340 mm Height 2.286 mm	Lenght 11.909 mm Width 2.223 mm	26.580 kgs 3.800 kgs	-
Flat Rack	Max. height of cargo	Floor dimensions	Dimensions between stanchions	Max. payload Tara weight	-
20' Dry Cargo (DC) 	2.245 mm	Lenght 5.966 mm Width 2.365 mm Height of floor 0.370 mm	Lenght 5.702 mm Width 2.200 mm	27.150 kgs 2.850 kgs	-
20' Dry Cargo (DC) 	2.275 mm	Lenght 12.060 mm Width 2.365 mm Height of floor 0.648 mm	Lenght 11.660 mm Width 2.200 mm	39.300 kgs 5.700 kgs	-

The above container information is just intended for informational purposes only and real dimensions may vary.